



TRACER WIRE DETAIL

CONDUCTIVE TYPE PIPE LOCATOR/TRACER WIRE SHALL BE INSTALLED TO LOCATE ALL SEWER LATERALS. THE WIRE SHALL EXTEND THE ENTIRE LENGTH OF THE PROPOSED LATERAL. THE WIRE SHALL BE INSTALLED DIRECTLY ON TOP THE PIPE AND SECURED TO THE LATERAL BY TAPE AT BASE OF RISER, SEWER MAIN AND EVERY 15'. CORROSION PROOF/FILLED WIRE CONNECTORS SHALL BE USED AT SPLICE LOCATIONS. ELECTRICAL TAPE SHALL BE USED AND NO BARE WIRE SHALL BE EXPOSED. TEST STATIONS SHALL BE INSTALLED INSIDE ALL CLEANOUT VAULTS AND EXISTING WIRES SHALL BE CONNECTED. ZINC OR MAGNESIUM ANODES SHALL BE ATTACHED AT BOTH THE BEGINNING AND THE END OF THE TRACER WIRE. A TYPICAL LAYOUT OF THE LOCATOR WIRE AND CLEANOUT IS PROVIDED IN THE FIGURE ABOVE. CONDUCTIVITY TO BE TESTED BEFORE ACCEPTANCE.